



Miniflex, 6kVA rack



Miniflex with Static switch, 6kVA rack

CE+T is now launching the Miniflex range, a brand new inverter for 48VDC applications with 120 or 230VAC output.

State-of-the-art technology has been integrated in this product to ensure high reliability and efficiency, while the cost per VA has been reduced to the minimum. Active load sharing and high level of local intelligence (full DSP control) will guarantee the reliability and efficiency you require for your applications.

This High Density Inverter can be used in different configurations, and supply loads up to 6kVA. Each module has an output power of 1000VA, and the racks system allows connecting in parallel up to 6 modules. Static switch can be ordered as an option, and will be integrated in specific rack system with included manual by-pass. Several distribution options exists, from the simple bulk output to specifically designed racks with breakers or standard plugs.

General features

- High efficiency, Patented technology
- Hot swap capability
- Full Digital Signal Processing control
- Parallel operation in True Redundant System
- Active load sharing and several disconnection levels
- Systems of 2, 4 or 6 modules with or without static switch

CE+T

Rue du Charbonnage, 18
Belgium - 4020 Wandre

<http://www.cet.be/Miniflex>

Tél : +32 (0)4 345 67 00
Fax : +32 (0)4 345 67 01

The smart AC solution

Miniflex System



Module specifications		
	120 VAC output	230 VAC output
1. Input specifications		
Operating voltage range, adjustable	40 VDC to 60 VDC	
Maximum Input current @40VDC, 800W	23 A	
Iin max. at Uin=48V, 100% overload	37 A	
Inrush current	< I nom.	
2. Output specifications		
Nominal output voltage	120VAC (108→127VAC)	230VAC (208→240VAC)
Output voltage tolerance	+ 3% of adjusted nominal voltage	
Output voltage frequency	50Hz or 60 Hz selectable (±0.01Hz)	
Overall distortion rate	< 3% on linear load	
Total transient recovery time	< 0,3 msec (Typical)	
Turn on delay	< 3 sec	
Nominal value of output current	8,3 A	4,4 A
Short circuit output current (Typical)	23A	12,3 A
Crest factor at nominal power	3:1	
Response time	< 500 µSec for 0→100% or 100→0% load transient	
3. Output power		
Nominal value	800W / 1000VA	
Permanent overload (rated in W)	125%	
Overload (+/- 15%, 5 sec. Max, Self-protected)	2000W / 2000VA	
Power factor influence	Full power output (1000VA) with Pf from 0 to 0,8 Limited to 800W with Pf from 0,8 to 1	
4. Electro magnetic compatibility		
Standards applied for immunity	EN 61000 – 4-2 / 4-3 / 4-4 / 4-5 / 4-6	
Standards applied for emission	ETS300-132-2 EN55022 ClassB	
5. Efficiency (@ full load)		
	> 90%	
6. Temperature		
Storage temperature	-40° to 80°C	
Permissible ambient temperature	-20° to 50°C	
7. MTBF (according MIL-HDBK 217F)		
	>177.000h fans included (> 258.000h without fans)	
8. Dielectric strength		
	4300 Vdc input/output - 4300 Vdc output/ground 2100 Vdc input/ground	
9. Safety		
	EN 60950 / UL 1950	
10. Dimensions / Weight		
	19 inches wide / 1U height / 350mm depth / 5Kgs	

CE+T

Rue du Charbonnage, 18
Belgium - 4020 Wandre

<http://www.cet.be/Miniflex>

Tél : +32 (0)4 345 67 00
Fax : +32 (0)4 345 67 01

The smart AC solution

Miniflex System



Static switch specifications		
	120 VAC output	230 VAC output
1. Input specifications		
Operating voltage range	90 to 150 Vrms	180 to 275 Vrms
Input frequency range (Selectable)	47,5 ... 52,5 Hz or 57,5 ... 62,5 Hz	
2. Maximum permanent current		
	50A (natural cooling conditions)	
3. Transfer performance		
Maximum voltage interruption	0 to 6 msec (Typical : 3 msec)	
Total transient voltage duration (max)	1 to 12 msec (Typical : 5 msec)	
4. Efficiency (@ full load)		
	> 98%	
5. Voltage conformity (rms)		
Maximum mains, adjustable	130 ... 150V	245 ... 265V
Minimum mains, adjustable	90 ... 110V	120 ... 215V
Maximum inverters, adjustable	130 ... 150V	245 ... 265V
Minimum inverters, adjustable	90 ... 110V	120 ... 215V
Load level to come back after overload	97 %	
6. Electro magnetic compatibility		
Standards applied for immunity	EN 61000 – 4-2 / 4-3 / 4-4 / 4-5 / 4-6	
Standards applied for emission	FCC Patr 15 class A / CISPR22 ClassB	
7. Temperature		
Storage temperature	-40° to 80°C	
Permissible ambient temperature	-20° to 50°C	
8. MTBF (according MIL-HDBK 217F)		
	> 400 000h	
9. Supervision possibility		
	With SYS3000 controller	
10. Signalling and measurements		
	11 LEDs	
	2 free potential contacts NO/NC – all contacts are doubled	
11. Safety		
	EN 60950 / UL 1950 / UL 1778 (Rack)	
12. Dimensions (WxDxH, mm) / Weight		
	316 x 360 x 86mm (2U) / 4 Kgs	

Subrack specifications		
	With Static Switch	Without Static Switch
2 modules* (W x D x H / Weight)	480 x 380 x 177,2mm / 5 Kgs	480 x 380 x 87,5mm / 3 Kgs
4 modules* (W x D x H / Weight)	480 x 380 x 265,2mm / 6,5 Kgs	480 x 380 x 178,2mm / 4,5 Kgs
6 modules* (W x D x H / Weight)	480 x 380 x 353mm / 8 Kgs	480 x 380 x 266mm / 6 Kgs
(*) 23" mounting accessories available as an option		

CE+T

Rue du Charbonnage, 18
Belgium - 4020 Wandre

<http://www.cet.be/Miniflex>

Tél : +32 (0)4 345 67 00
Fax : +32 (0)4 345 67 01

The smart AC solution